

ATLANTIS STANDARD 10 bar

ATLANTIS STANDARD 14.0

ATLANTIS STANDARD 19.0


ATLANTIS STANDARD 21.0

Technical data		
Power supply	V-Hz	400 - 50/60
Start-up time	min	4
Boiler capacity	l	7.3 - 12.0
Boiler material		AISI 304
Boiler power	Kw	7.3:14.0 Kw - 12:19.0 - 21 Kw
Steam product quantity	g/min	385 - 560 - 600
Steam output regulation	g/min	5 - 210 / 5 - 235
Steam pressure	bar	10,0 ± 0,3
Steam boiler temperature	°C	180
Unlimited autonomy		yes
Double safety valve PED 2	bar	11,0 ± 0,3
Control steam flow	bar	10,0/6,0 ± 0,3
Thermostat	°C	230
PCB	V	230/12
Control panel voltage	V	5
Power cable lenght	m	10
Frame material		stainless steel 18/10
Standard wheels	Ø	150
Dimensions	mm	710x530x830
Weight	Kg	+/- 50

Hot water output		yes
Electronic hot water control		yes
Detergent output		yes
Detergent output regulation		yes
Water tank	l	29
Detergent tank	l	8,5



Optional
Vacuum system



Optional


Pneumatic wheels Ø 200 mm

Vacuum system

Double operator

ATLANTIS STANDARD 10 bar

Vacuum/steam + chemical + water handle grip




4 m

6 m


8 m

Steam/vacuum kit


Floor brush 400 plus




Dust chassis 400 plus




Liquid vacuum chassis 400 plus



Upholstery chassis 400 plus




Glass washer 150




Bristled brush insert 150




Rubber insert 150



Glass washer 250



Steam lance plus



Steam lance adaptor plus



Ø 30 brushes plus



Ø 60 brushes



Flat lance



Nozzle 80 plus




Plunger



Trasparent nozzle




Novaltec Multigrass Spryer



Filler tunnel




Anti-scale vials



10 pz

Rigid extensions plus



OPTIONAL

Vacuuming steam brush soft bristle



Vacuuming steam lance soft bristle



Trasparent nozzle large




ATLANTIS STANDARD 10 bar

steam + water + chemical EVO handle grip




4 m 6 m 8 m

Medium straight rigid extension




900 mm

Medium curved rigid extension



450 mm

Long straight rigid extension



1050 mm

Short curved rigid extension



250 mm

Ø 50 brushes



Nylon



Steel



Brass



Stainless steel



TYNCS


Brass nozzle



Scraper steam nozzle



Rectangular brush for steam 350 mm




Barrique washer




Kit car wash

Glass washer 150



Bristled brush insert 150



4 pz

Rubber insert 150



Steam lance plus



Ø 30 nylon brushes plus



4 pz

Flat lance



Nozzle 80 plus



Trasparent nozzle



Vacuuming steam brush soft bristle



Vacuuming steam lance soft bristle



Novaltec Group S.r.l

Sede Amministrativa e Produzione: Via Pier Santi Mattarella, 28 - 30030 Gardigiano di Scorzè - Venezia
T - +39 041 449949 F - +39 041 5830575 / info@novaltegroup.com / www.novaltegroup.com